



Europäisches Patentamt
European Patent Office
Office européen des brevets



⑪ Publication number: **0 429 123 B1**

⑫

EUROPEAN PATENT SPECIFICATION

- ④⑤ Date of publication of patent specification: **27.12.95** ⑤① Int. Cl.⁸: **C07C 69/593, C07C 67/347, C10M 105/36, C10M 107/28, C10M 129/72, C10M 145/16**
- ②① Application number: **90202980.0**
- ②② Date of filing: **12.11.90**

- ⑤④ **Compositions from alpha,beta-unsaturated dicarboxylic acid esters and olefinically unsaturated compounds which are particularly suitable for use as lubricants and lubricant additives and a process for the preparation of such compositions**

- ③① Priority: **17.11.89 EP 89202923**
17.11.89 EP 89202924
- ④③ Date of publication of application:
29.05.91 Bulletin 91/22
- ④⑤ Publication of the grant of the patent:
27.12.95 Bulletin 95/52
- ⑧④ Designated Contracting States:
AT BE CH DE DK ES FR GB GR IT LI LU NL SE
- ⑤⑥ References cited:
EP-A- 0 075 217
GB-A- 954 901
GB-A- 1 173 643
US-A- 4 235 786

- ⑦③ Proprietor: **Akzo Nobel N.V.**
Velperweg 76
NL-6824 BM Arnhem (NL)
- ⑦② Inventor: **Wallfahrer, Uwe Hans**
Froitscheiderstrasse 54
D-5168 Nideggen (DE)
Inventor: **Verploegh, Marius Cornelis**
Auf der Neuen Ahr 5
D-5166 Kreuzau (DE)
Inventor: **Macherey, Heribert Josef**
Altenweiher 15
D-5166 Kreuzau (DE)
- ⑦④ Representative: **Schalkwijk, Pieter Cornelis et al**
AKZO NOBEL N.V.
Patent Department (Dept. CO)
P.O. Box 9300
NL-6800 SB Arnhem (NL)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

The present invention relates generally to compositions produced from α,β -unsaturated dicarboxylic compounds and olefinically unsaturated compounds, which compositions possess properties making them particularly suitable for use as lubricants and lubricant additives.

Compositions comprising reaction products of α,β -unsaturated dicarboxylic compounds and olefinically unsaturated compounds are generally known in the art. These reaction products have been described in the literature as having a large number of uses ranging from lubricants to emulsifiers, coating additives to cosmetics, protective colloids to dispersants, and detergents to plasticizers.

One particular type of such reaction products, i.e. intermediates in the production of polycondensation products, is known from GB 1 173 643. This reference discloses a specific, high pressure process which produces unsaturated tetracarboxylic acids by reacting an olefin with a 1,2-unsaturated 1,2-dicarboxylic acid or a functional derivative thereof. Suitable reactants to produce the tetracarboxylic acids are lower alkyl olefins. Preferred are β -branched olefins, with the olefin exemplified being isobutene.

The prior art further describes several schemes for reacting α,β -unsaturated dicarboxylic and olefin compounds; however, the compositions produced by these known reaction schemes comprise essentially one or both of only two types of reaction products - lower molecular weight ene (alkenyl succinic) products and higher molecular weight polymerization products.

When reacting α,β -unsaturated dicarboxylic compounds with olefins, the difference between producing the lower molecular weight alkenyl succinic product and the higher molecular weight polymerization products is normally due to the presence or absence of a polymerization initiator in the reaction mixture.

For example, US4192930, DE-A-3223694, EP-B-0075216 and JP Laid-Open 80/157687 (all of which are incorporated by reference herein for all purposes) teach the production of the higher molecular weight polymerization products by reacting α,β -unsaturated dicarboxylic compounds and olefins in the presence of polymerization initiators such as peroxy compounds.

On the other hand, GB1055337 (incorporated by reference herein for all purposes) teaches the production of alkenyl succinic compounds (and the hydrogenated alkyl succinic corresponding compounds) by reacting the above-mentioned components without the polymerization initiator.

To improve the efficiency of the ene reaction and increase selectivity toward the alkenyl succinic products, US3819660, US4255340, US4396774 and US4761488 (all of which are incorporated by reference herein for all purposes) teach the reaction of α,β -unsaturated dicarboxylic acids and anhydrides with olefins in the presence of particular ene reaction catalysts (accelerators).

To achieve like results in increasing selectivity toward alkenyl succinic anhydrides, US3412111, US4581464 and JP Laid Open 82/32276 (all of which are also incorporated by reference herein for all purposes) teach the addition of a particular polymerization inhibitor to the reaction of α,β -unsaturated dicarboxylic anhydrides and olefins. As indicated in the examples of US3412111, the use of the polymerization inhibitor does indeed appear to significantly improve selectivity toward the alkenyl succinic product.

Long chain hydrocarbyl polysuccinic anhydrides are known from US 4 720 555, in which a method is disclosed which comprises the reaction of a long chain hydrocarbon with an excess of maleic anhydride in the absence of a solvent.

Further it is mentioned that a process for the preparation of substituted carboxylic acids wherein a mono olefin is reacted with an unsaturated, conjugated dicarboxyl compound is known from GB 954 901. The obtained products are useful as rust inhibitors in lubricating oils.

It should be noted that generally α,β -unsaturated dicarboxylic acid esters are recognized to be less reactive with olefins than their acid and anhydride counterparts. This prejudice to the use of esters in an ene selective reaction scheme is also apparent from previously mentioned GB 1 173 643. The unsaturated carboxylic compounds exemplified therein, diethyl esters of maleate and fumarate, do react to form the specific tetracarboxylic acid, but the conversion is poor. Previously mentioned GB 954 901 makes a distinction between various carboxylic compounds and, in line with further prior art, does not actually make use of esters, teaching that carboxylic anhydrides are to be preferred. In view of their low reactivity, esters are further utilized only in the polymerization reactions as described, for example, in previously incorporated DE-A-3223694.

It has now surprisingly been discovered that, using the appropriate esters and olefins, compositions can be prepared as is further described below which comprise a substantial amount of an intermediate molecular weight reaction product which is neither the known lower molecular weight alkenyl succinic nor the known higher molecular weight polymeric reaction product.

Summary of the Invention

In accordance with the present invention, there is provided a composition suitable for use as a lubricant or lubricant additive, which composition comprises the reaction product of (1) an α,β -unsaturated dicarboxylic compound and (2) an olefinically unsaturated compound, characterized in that the α,β -unsaturated dicarboxylic compound (1) comprises at least one of a fumaric or maleic ester, wherein the esterifying component comprises a monoalcohol having from 4 to 20 carbon atoms, the olefinically unsaturated compound (2) comprises a monoolefinically unsaturated compound having from 12 to 24 carbon atoms, and the composition comprises a substantial amount of a reaction product of (1) and (2) which comprises:

- at least 30% by weight of a product (3) that is neither the ene reaction product nor the polymerization product of (1) and (2), the reaction product (3) having an intermediate molecular weight which is higher than that of the corresponding ene reaction product and lower than that of the corresponding polymerization product, and which is in the range of from 600 to 1500,
 - up to 70% by weight of the lower molecular weight ene reaction product of components (1) and (2),
- wherein the intermediate molecular weight reaction product (3) does not comprise compounds incorporating more than 5 monomeric units.

In order to prepare the compositions in accordance with the present invention generally three routes can be followed, viz. (i) reacting (1) and (2) in the presence of a polymerization inhibitor, (ii) reacting (1) and (2) under the exclusion of oxygen, or (iii) stepwise dosage of the ester (1) to the reaction mixture comprising olefin (2). In order to prepare the compositions in accordance with the present invention said routes may be combined in any possible manner, e.g. stepwise dosage of the ester (1) to the reaction mixture comprising olefin (2) and a polymerization inhibitor.

As further detailed below, the compositions in accordance with the present invention are preferably produced by reacting (1) and (2) in the presence of an effective amount of a polymerization inhibitor.

Due to their desirable properties, the compositions in accordance with the present invention find utility in a wide variety of fields ranging, for example, from lubricants to emulsifiers, coating additives to cosmetics and detergents to plasticizers. As indicated before, however, they have been found especially suitable for use as lubricants and lubricant additives, particularly in low viscosity lubricant applications such as in engine oils, gear oils, greases, compressor oils, turbine oils, metal working fluids, machine oils and hydraulic fluids.

As mentioned above, both the lower molecular weight ene reaction products (alkenyl succinic compounds and corresponding hydrogenated alkyl succinic compounds) as well as the higher molecular weight polymerization and hydrogenated polymerization products are well known as lubricants and lubricant additives. When used in the aforementioned lubricant applications, however, each has its shortcomings.

For example, the alkenyl and alkyl succinic compounds are characterized by high volatility, high color, high acid values, very low viscosity and less than optimal lubrication performance.

While the polymerization products have generally been found to be more suitable for use in this area, they still suffer from the disadvantage of high viscosities, which may be limiting to their ability to be used in the aforementioned low viscous lubricant applications.

The compositions in accordance with the present invention overcome these disadvantages by providing a balance of desirable properties such as, for example, viscosity, viscosity index, pour point, volatility and lubricity, which would not be expected based upon the properties of the known lower molecular weight alkenyl and alkyl succinic products and higher molecular weight polymerization products.

These and other features and advantages of the present invention will be more readily understood by those skilled in the art from a reading of the following detailed description.

Detailed Description of the Preferred Embodiments

As just mentioned, in accordance with the present invention there is provided a composition suitable for use as a lubricant or lubricant additive, which composition comprises the reaction product of (1) an α,β -unsaturated dicarboxylic compound and (2) an olefinically unsaturated compound, characterized in that the α,β -unsaturated dicarboxylic compound (1) comprises at least one of a fumaric or maleic ester, wherein the esterifying component comprises a monoalcohol having from 4 to 20 carbon atoms, the olefinically unsaturated compound (2) comprises a monoolefinically unsaturated compound having from 12 to 24 carbon atoms, and the composition comprises a substantial amount of a reaction product of (1) and (2) which comprises:

- at least 30% by weight of a product (3) that is neither the ene reaction product nor the polymerization product of (1) and (2), the reaction product (3) having an intermediate molecular weight which is

higher than that of the corresponding ene reaction product and lower than that of the corresponding polymerization product, and which is in the range of from 600 to 1500,

- up to 70% by weight of the lower molecular weight ene reaction product of components (1) and (2), wherein the intermediate molecular weight reaction product (3) does not comprise compounds incorporating more than 5 monomeric units.

As indicated above, suitable α,β -unsaturated dicarboxylic compounds are fumaric and maleic esters, which includes both the monoesters and diesters of fumaric acid, maleic acid and maleic anhydride. The diesters, however, are preferred due to their better stability under more severe conditions. Especially preferred are the fumaric diesters.

As suitable monoalcohols having from 4 to 20 carbon atoms (esterifying components for the fumaric and maleic esters) may be mentioned linear, branched and/or cyclic monoalcohols such as butanols, ethylhexanols, neopentyl alcohols, isodecyl alcohols, phenols and cyclohexanols. More preferred of these are the monoalcohols having from 4 to 12 carbon atoms, and especially from 4 to 8 carbon atoms. Most preferred are 1-butanol and 2-ethylhexanol. Further, it is advantageous to make use of alcohols alkoxylated with from 1 to 10 ethoxy or propoxy units. The original alcohol moiety may then have from 1 to 20 carbon atoms.

The fumaric and maleic esters, component (1) above, may be produced by the esterification of the appropriate of fumaric acid, maleic acid or maleic anhydride. Such esterification reaction is well known to those skilled in the art and need not be further detailed herein.

As suitable monoolefins having from 12 to 24 carbon atoms, component (2) above, may be mentioned a wide variety of α -olefins, internal olefins and vinylidene compounds, as well as other branched, aromatic and heterosubstituted monoolefins and mixtures thereof, a number of which are specifically disclosed in many of the previously incorporated references. Particularly preferred are α -olefins, internal olefins and vinylidene compounds having from 12 to 16 carbon atoms, an advantage to these olefins being that products are obtained which exhibit a lower pour point.

It should be noted that commercially available olefins are generally mixtures characterized by a predominant olefin species and a predominant or average carbon number content. Such commercially available mixtures comprising in substantial part α -olefins with minor amounts of internal olefins and vinylidene compounds are particularly preferred.

As specific examples of suitable α -olefins may be mentioned 1-dodecene, 1-tetradecene, 1-hexadecene and 1-octadecene. Preferred among these are the C_{12} to C_{16} α -olefins, with the C_{14} to C_{16} α -olefins being most preferred.

In the preferred reaction scheme, components (1) and (2) are reacted in the presence of an effective amount of a suitable polymerization inhibitor. As examples of such may be mentioned the hydroxy aromatic and amino aromatic compounds as disclosed in previously incorporated US3412111. Of these, hydroquinone, p-tert-butylcatechol and p-hydroxyanisole are preferred, with hydroquinone being most preferred.

By "effective amount" is meant an amount of polymerization inhibitor sufficient to result in the production of a substantial amount of the intermediate molecular weight reaction product. The amount of inhibitor utilized, therefore, may vary widely, but is preferably in the range of from about 0.01% to about 3% by weight, more preferably from about 0.05% to about 2% by weight, and most preferably from about 0.1% to 1% by weight, based upon the combined weight of components (1) and (2).

It is also preferred that the reaction of components (1) and (2) should take place in the substantial absence of the well-known polymerization initiators, such as those known from the previously incorporated references.

The reaction between components (1) and (2), in the presence of the polymerization inhibitor, is preferably conducted at temperatures from about 180°C to about 350°C and, more preferably, from about 200°C to about 270°C. The reaction may be carried out at subatmospheric, atmospheric or superatmospheric pressures, but preferably atmospheric. The reaction preferably is carried out in the absence of oxygen, i.e. under an inert (nitrogen) atmosphere. Reaction times may vary widely, generally ranging from about 0.5 to about 15 hours and, more preferably, from about 5 to about 12 hours, with the longer reaction times required for the lower reaction temperatures.

Components (1) and (2) may be reacted in widely varying molar ratios, but generally ranging from about 0.15/1 to about 6.0/1, preferably from about 0.25/1 to about 4.0/1, and more preferably from about 0.5/1 to 2.0/1. Components (1) and (2) may be reacted in a single dose or may be dosed continuously or periodically throughout the reaction cycle. Stepwise dosing of component (1) to the reaction mixture containing (2) is preferred.

The compositions resulting from the reaction of components (1) and (2), when produced in accordance with the present invention, comprise a substantial amount of an intermediate molecular weight reaction product, which is distinguishable from the known lower molecular weight ene reaction product and higher molecular weight polymerization reaction products of the same components. The compositions produced in accordance with the present invention may also contain amounts of one or more of these known lower and higher molecular weight products.

More specifically, the compositions in accordance with the present invention comprise at least about 30% by weight, preferably at least about 40% by weight, and more preferably at least about 50% by weight, of the intermediate molecular weight reaction product, and up to about 70% by weight, preferably up to about 60% by weight, and more preferably up to about 50% by weight, of the lower molecular weight reaction product. % by weight is based upon the total weight of the reaction products.

It has been found that the intermediate molecular weight reaction product primarily comprises compositions of 3-5 monomeric units, the intermediate molecular weight reaction product overall having a number average molecular weight (M_n) in the range of about 600 to about 1500. Further, it has been found that, of these compositions having 3-5 monomeric units, a greater proportion of the monomeric units are ester-based monomeric units.

It is believed that the intermediate molecular weight reaction product includes compositions such as:

(a) a lower intermediate molecular weight "tandem ene" reaction product, which comprises 3 monomeric units (1 olefin-based unit and 2 ester-based units), as well as,

(b) higher intermediate molecular weight oligomerization and/or "multi-ene" products, which comprise 4-5 monomeric units (generally with a greater proportion of ester-based units than olefin-based units).

Such intermediate molecular weight reaction products are not known from the previously incorporated references, nor can they be produced in a reasonable manner by the reaction schemes disclosed therein.

The compositions in accordance with the present invention may additionally be hydrogenated, for example by heating at 130 - 200 °C in the presence of a catalyst, e.g., nickel or palladium. An advantage to hydrogenated compositions according to the invention is the improvement of their thermo-oxidative stability. Hydrogenation of these types of compositions is well-known in the art, and need not be detailed further.

It is clear, as demonstrated below, that the compositions in accordance with the present invention possess properties making them distinguishable from those compositions produced in accordance with the known "ene" selective reactions or the known polymerization selective reactions.

These and other aspects of the present invention will be further exemplified by the following specific examples offered by way of illustration and not limitation thereof.

EXAMPLES

In the following examples, compositions were produced from different α,β -unsaturated dicarboxylic compounds and olefinically unsaturated compounds as set forth below and in Tables I-XII.

PART I:

Experimental and comparative evidence directed to the polymerization inhibitor embodiment.

The various compounds were reacted via the following four different reaction schemes:

Invention - ester + olefin in the presence of a polymerization inhibitor and in the presence of oxygen

Alternative A - anhydride (or acid) + olefin in the presence of a polymerization inhibitor (Step 1), with subsequent esterification (Step 2)

Alternative B - ester + olefin without a polymerization inhibitor and in the presence of oxygen

Alternative C - ester + olefin in the presence of a polymerization initiator and in the presence of oxygen

The resulting compositions (1) were tested for:

(2,3) product composition (wt% ene reaction product and other reaction products) - by means of gel permeation chromatography (GPC);

(4) number average molecular weight (M_n) of the other reaction products - also by means of GPC;

(5,6) viscosity at 40 °C and 100 °C (cSt) - according to ASTM D445;

(7) viscosity index - calculated according to ASTM D2270-79;

(8) acid value (mg KOH/g product) - according to ASTM D 974;

(9) color - by visual inspection;

- (10) iodine value - according to DIN 53241;
 (11) pour point (°C) - according to DIN ISO 3016; and
 (12) pour point hydrogenated (°C) - the products were subsequently hydrogenated with PD/C as catalyst, at 150°C, under normal pressure and for about 3 hours. The hydrogenated products were tested for pour point as above.

Process in Accordance with the Present Invention - Examples 1-8

Into a suitable reaction vessel were added:
 3 moles of olefin,
 3 moles of fumaric diester,
 xylene (1% of total weight) and
 hydroquinone (0,3% of total weight),
 The mixture was then heated to 230°C for 10 hours, after which the remaining volatiles were removed up to 240°C in vacuo.
 The product yield for the process in accordance with the present invention was, in each case, between about 70%-75%. Product yield in these examples is based upon the total weight of the raw materials.

Alternative A - Comparative Examples A1-A8

Step 1 - reaction of maleic anhydride and olefin in the presence of polymerization inhibitor

Into a suitable reaction vessel were added:
 3 moles of olefin,
 3 moles of maleic anhydride and
 hydroquinone (0,3% of total weight),
 which were heated to reflux. As the reaction proceeded, the reflux temperature gradually increased (typically to about 230°C after three hours) and the reaction was continued to completion (typically about another 4 hours at 230°C). The resulting product, which comprised essentially the alkenyl succinic anhydride, was subsequently purified by vacuum distillation.
 The product yield after Step 1 was, in each case, between about 70%-75%.

Step 2 - esterification of product from Step 1

2 moles of the product from Step 1, 6 moles of an alcohol, 400 g toluene and p-toluenesulfonic acid (about 0,15% of the total weight) were heated to reflux temperature. The water of reaction was removed by means of a Dean-Stark trap. The reaction was complete when no more water was formed (typically about 7 hours). The remaining volatiles were then removed up to 240°C in vacuo.

Alternative B - Comparative Examples B1-B8

The reaction was carried out as described above for the process in accordance with the present invention, except that no polymerization inhibitor or xylene was added to the reaction mixture.
 The product yield was, in each case, between about 70%-75%.

Alternative C - Comparative Examples C1-C8

Into a suitable reaction vessel were added:
 3 moles of olefin and
 3 moles of fumaric diester,
 the mixture being heated to 230°C. At this temperature, 0,03 moles (total) of di-t-butylperoxide were added in 10 portions, one portion every 20 minutes. After the addition of the last portion, the contents were kept at 230°C for an additional hour, then the remaining volatiles were removed up to 240°C in vacuo.

EP 0 429 123 B1

The product yield was, in each case, between about 85%-90%.

TABLE I
Olefin = α -C₁₂
Esterifying Component = n-butanol

		1	A1	B1	C1
(1)	Example				
(2)	wt% ene product	40	100	5	4
(3)	wt% other products	60	0	95	96
(4)	Mn other products	1100	----	3350	1350
(5)	viscosity @ 40°C	63,8	10,5	157	119,1
(6)	viscosity @ 100°C	9,49	2,78	18,0	14,7
(7)	viscosity index	130	108	127	126
(8)	acid value	0,8	3,3	1,1	0,62
(9)	color	yellow	brown	yellow	yellow
(10)	iodine value	24	65	15	14
(11)	pour point (°C)	<-50	<-50	-34	-44
(12)	pour point (°C)	-34	-36	-22	-45
	hydrogenated				

TABLE II

Olefin = α -C_{14/16}

Esterifying Component = n-butanol

5

		2	A2	B2	C2
(1)	Example				
(2)	wt% ene product	44	100	12	7
(3)	wt% other products	56	0	88	93
(4)	Mn other products	1100	----	1350	1300
(5)	viscosity @ 40°C	40,2	14,0	104	100,0
(6)	viscosity @ 100°C	6,9	3,40	13,5	13,1
(7)	viscosity index	132	118	128	128
(8)	acid value	0,7	5,3	0,9	0,78
(9)	color	yellow	brown	yellow	yellow
(10)	iodine value	35	59	20	15
(11)	pour point (°C)	<-50	<-51	-36	-33
(12)	pour point (°C)	-33	-28	-32	-28
	hydrogenated				

30

TABLE III

Olefin = α -C₁₆

Esterifying Component = n-butanol

35

		3	A3	B3	C3
(1)	Example				
(2)	wt% ene product	40	100	3	5
(3)	wt% other products	60	0	97	95
(4)	Mn other products	1200	----	1420	1400
(5)	viscosity @ 40°C	35,2	14,8	240	117,4
(6)	viscosity @ 100°C	6,7	3,69	24,7	15,3
(7)	viscosity index	145	142	130	135
(8)	acid value	0,8	2,4	---	0,6
(9)	color	yellow	brown	yellow	yellow
(10)	iodine value	35	58	13	15
(11)	pour point (°C)	-44	-31	---	-12
(12)	pour point (°C)	-17	-10	---	-11
	hydrogenated				

55

TABLE IV

Olefin = α -C_{20/24}

Esterifying Component = n-butanol

5

		4	A4	B4	C4
10	(1) Example				
	(2) wt% ene product	41	95	7	6
	(3) wt% other products	59	51	93	94
	(4) Mn other products	1380	----	1600	1600
	(5) viscosity @ 40°C	55,2	40,6	207	150,6
15	(6) viscosity @ 100°C	9,3	6,81	20,1	18,4
	(7) viscosity index	151	125	112	137
	(8) acid value	0,8	5,0	1,2	0,8
20	(9) color	brown	brown	brown	brown
	(10) iodine value	27	37	13	14
	(11) pour point (°C)	+17	+15	>+20	+20
25	(12) pour point (°C)	+20	+20	>+20	>+20
	hydrogenated				

1=portions not removeable during Step 1 purification

30

35

40

45

50

55

TABLE V

Olefin = α -C₁₂

Esterifying Component = 2-ethylhexanol

(1) Example	5	A5	B5	C5
(2) wt% ene product	35	100	15	4
(3) wt% other products	65	0	85	96
(4) Mn other products	1400	----	1500	1350
(5) viscosity @ 40°C	84,4	18,8	206	138,7
(6) viscosity @ 100°C	10,9	3,98	21,0	15,7
(7) viscosity index	116	108	121	118
(8) acid value	1,3	1,5	1,4	1,0
(9) color	yellow	brown	yellow	yellow
(10) iodine value	34	51	13	14
(11) pour point (°C)	<-50	<-50	-36	-40
(12) pour point (°C)	-45	-52	-36	-42
hydrogenated				

TABLE VI

Olefin = α -C_{14/16}

Esterifying Component = 2-ethylhexanol

(1) Example	6	A6	B6	C6
(2) wt% ene product	52	100	21	8
(3) wt% other products	48	0	79	92
(4) Mn other products	1340	----	1400	1400
(5) viscosity @ 40°C	40,6	24,8	128	122,2
(6) viscosity @ 100°C	6,7	4,78	14,9	14,5
(7) viscosity index	118	114	119	120
(8) acid value	1,0	6,5	1,4	1,4
(9) color	yellow	brown	yellow	yellow
(10) iodine value	30	48	13	14
(11) pour point (°C)	<-50	<-55	-42	-38
(12) pour point (°C)	<-40	-53	-44	-38
hydrogenated				

TABLE VII

Olefin = α -C₁₆

Esterifying Component = 2-ethylhexanol

5

10

15

20

25

30

35

40

45

50

55

(1) Example	7	A7	B7	C7
(2) wt% ene product	48	100	10	5
(3) wt% other products	52	0	90	95
(4) Mn other products	1100	----	1600	1450
(5) viscosity @ 40°C	49,6	24,8	173	138,2
(6) viscosity @ 100°C	7,8	5,02	18,9	16,0
(7) viscosity index	124	132	123	122
(8) acid value	1,0	1,1	1,4	1,0
(9) color	yellow	brown	yellow	yellow
(10) iodine value	29	46	12	14
(11) pour point (°C)	<-50	<-50	-36	-18
(12) pour point (°C)	-26	-36	-34	-18
hydrogenated				

TABLE VIII

Olefin = α -C_{20/24}

Esterifying Component = 2-ethylhexanol

(1) Example	8	A8	B8	C8
(2) wt% ene product	50	95	8	8
(3) wt% other products	50	51	92	92
(4) Mn other products	1500	----	1900	1650
(5) viscosity @ 40°C	82,0	55,1	266	192,3
(6) viscosity @ 100°C	11,2	8,86	26,7	21,4
(7) viscosity index	126	138	131	133
(8) acid value	2,4	8,6	2,0	1,3
(9) color	brown	brown	brown	brown
(10) iodine value	24	44	11	13
(11) pour point (°C)	+14	+04	+15	+20
(12) pour point (°C)	+20	+03	+16	+16
hydrogenated				

1=portions not removeable during Step 1 purification

These results show a clear distinction between the compositions in accordance with the present invention as compared to the lower molecular weight alkenyl and alkyl succinic reaction products (Alternate A), and higher molecular weight polymerization products (Alternates B and C) produced in accordance with the alternative processes. That such a divergence in product composition and properties would exist with just a minor variance in the apparent product composition is, in and of itself, clearly unexpected.

Additionally, these results clearly show that the "other" products, which comprise a substantial amount of the compositions in accordance with the present invention, are neither the lower molecular weight alkenyl succinic products nor the higher molecular weight polymerization products, and in fact are intermediate in molecular weight with respect thereto.

Comparative Examples D1 and D2

The following mixtures were made:

D1: mixture of A2 (ene product) and C2 (polymerization product)

D2: mixture of A6 (ene product) and C6 (polymerization product)

Various properties of these mixtures were measured as described above. Table IX below provides a comparison, respectively, of mixture D1 to the reaction product of Example 2, and mixture D2 to the reaction product of Example 6.

TABLE IX

(1) Example	2	D1	6	D2
(2) wt% ene product	44	44	52	52
(3) wt% other products	56	56	48	48
(4) Mn other products	1100	1300	1340	1400
(5) viscosity @ 40 ° C	40,2	67,8	40,6	70,2
(6) viscosity @ 100 ° C	6,9	10,8	6,7	10,1
(7) viscosity index	132	150	118	128
(11) pour point (° C)	<-50	-42	<-50	-34

These comparative examples further emphasize the difference in the reaction products in accordance with the present invention over those in accordance with the alternative processes. Particularly noteworthy is the clear demonstration that the "other" reaction products produced in accordance with the present invention are not the same as the polymerization reaction products, as mixtures in equal proportions with the ene product produce compositions with markedly different properties.

PART II

Experimental and comparative data on the various preparation methods

In Table X the results have been outlined of experiments establishing the influence of inhibitor presence, oxygen exclusion and ester dosage. The basic procedure was comprised of reacting 3 moles of C₁₆ α -olefin and 3 moles of dibutyl fumarate at 250 ° C. Varied were:

- 0.3% p-hydroxy anisole (present or not)
- oxygen (excluded or not)
- ester dosage

("no" means: added in one go and heated for 6 hours, "yes" means: dosed within 4 hours and heated for a further 2 hours)

TABLE X

Inhibitor present	oxygen present	ester dosed	product composition		viscosity (100 ° C)
			1:1 adduct	others	
yes (0,3%)	no	yes	53%	47%	5,72 cs
		no	53%	47%	5,67 cs
	yes	yes	36%	64%	8,27 cs
		no	30%	70%	9,65 cs
no	no	yes	44%	56%	6,75 cs
		no	40%	60%	7,04 cs
	yes	yes	30%	70%	9,74 cs
		no	10%	90%	14,3 cs

The table shows that products according to the invention are prepared provided the inhibitor is present, oxygen is excluded or the ester is dosed. The product at the bottom of the table is not in accordance with the present invention.

PART III

Influence of ester and olefin chain length

Basically following the procedure according to Part I, Examples 1-8 Comparative Examples E1-E4 were prepared. For clarity a comparison is made with Examples 1 and 2.

- 1: C₁₂ α -olefin and C₄ di ester (dibutyl fumarate)

- 2: C_{14/16} α -olefin and C₄ diester (dibutyl fumarate)
 E1: C₁₀ α -olefin and C₄ diester (dibutyl fumarate)
 E2: C₁₀ α -olefin and C₂ diester (diethyl fumarate)
 E3: C_{14/16} α -olefin and C₁ diester (dimethyl fumarate)
 5 E4: C_{14/16} α -olefin and C₁ diester (dimethyl maleate)

The results have been outlined in Table XI

TABLE XI

(1) Example	1	2	E1	E2	E3	E4
(2) wt% ene product	40	44	3%	15%	45%	30%
(3) wt% other products	60	56	91%	85%	55%	70%
(4) Mn other products	1100	1100	2200	2600, 20000	1000	1200
15 (5) viscosity at 40 ° C (cSt)	63,8	40,2	224	*)	103	176
(6) viscosity at 100 ° C(cSt)	9,49	6,9	24,6	*)	9,39	13,5
(7) viscosity index	130	132	138	*)	62	65
(11) pour point (° C)	<-50	<-50	-39	*)	-26	-24

20 *) In a poor yield (25%) a reaction product was obtained which displayed such inhomogeneity that measurements could not be conducted.

From Table XI it can be learned that the olefin chain length is critical for obtaining the favourably characterized products according to the invention, which is apparent from the unexpectedly large viscosity difference.

From Table XI it can further be learned that esters compounds having a chain shorter than C₄ prove unsuitable as a lubricant or lubricant additive on the basis of the low viscosity index. Further it is apparent that the products in accordance with the present invention exhibit much lower pour points than their analogues outside the scope of the invention.

PART IV

Various Experimental Data

35 Examples 9-11 (in accordance with the present invention)

(9)

40 Into a suitable reaction vessel were added:
 3 moles of C_{14/16} α -olefin
 p-hydroxy anisole (0.3 % of total weight),
 the mixture being flushed with nitrogen. The mixture was then heated to 250 ° C and 3 moles of dibutyl fumarate were added within a period of 4 hours. After a further period of 2 hours the remaining volatiles were removed at 240 ° C under vacuo.

(10)

50 The procedure according to Example 9 was followed, but with 6 moles C_{14/16} α -olefin (and 3 moles of dibutyl fumarate).

(11)

The procedure according to Example 9 was followed, but with 3 moles of di(methyl diglycol)fumarate replacing the dibutyl fumarate.

55 The results of Examples 9-11 have been outlined in Table XII

TABLE XII

(1) Example	9	10	11
(2) wt% ene product	52	50	45
(3) wt% other products	48	50	55
(4) Mn other products	1100	1000	1400
(5) viscosity at 40 ° C (cSt)	32,7	28,3	41,3
(6) viscosity at 100 ° C (cSt)	6,12	5,59	7,1
(7) viscosity index	137	140	135
(10) iodine value	35	36	32
(11) pour point (° C)	<-40 ° C	-39 ° C	not determined

Claims

1. A composition suitable for use as a lubricant or lubricant additive, which composition comprises the reaction product of (1) an α,β -unsaturated dicarboxylic compound and (2) an olefinically unsaturated compound, characterized in that the α,β -unsaturated dicarboxylic compound (1) comprises at least one of a fumaric or maleic ester, wherein the esterifying component comprises a monoalcohol having from 4 to 20 carbon atoms, the olefinically unsaturated compound (2) comprises a monoolefinically unsaturated compound having from 12 to 24 carbon atoms, and the composition comprises a substantial amount of a reaction product of (1) and (2) which comprises:
 - at least 30% by weight of a product (3) that is neither the ene reaction product nor the polymerization product of (1) and (2), the reaction product (3) having an intermediate molecular weight which is higher than that of the corresponding ene reaction product and lower than that of the corresponding polymerization product, and which is in the range of from 600 to 1500,
 - up to 70% by weight of the lower molecular weight ene reaction product of components (1) and (2),
 wherein the intermediate molecular weight reaction product (3) does not comprise compounds incorporating more than 5 monomeric units.
2. The composition according to claim 1, characterized in that component (2) comprises an α -olefin, internal olefin, vinylidene compound or a mixture thereof.
3. The composition according to claim 2, characterized in that component (2) comprises an olefin mixture comprising in substantial part an α -olefin with minor amounts of an internal olefin and a vinylidene compound.
4. The composition according to claim 2, characterized in that component (2) comprises from 14 to 16 carbon atoms.
5. The composition according to claim 1, characterized in that component (1) comprises a fumaric or maleic diester.
6. The composition according to claim 5, characterized in that component (1) comprises a fumaric diester.
7. The composition according to claim 1, characterized in that the esterifying component comprises a monoalcohol having from 4 to 8 carbon atoms.
8. The composition according to claim 7, characterized in that the esterifying component comprises a monoalcohol having 4 carbon atoms.
9. The composition according to claim 1, characterized in that the esterifying component comprises an alkoxyated monoalcohol.
10. The composition according to claim 9, characterized in that the monoalcohol comprises from 1 to 10 alkoxy units selected from the group consisting of ethoxy and propoxy.

11. The composition according to any one of the preceding claims, characterized in that it is in a hydrogenated form.
12. A lubricant or lubricant additive comprising the composition according to any one of claims 1-11.
- 5 13. A process for producing a composition according to claim 1, wherein
 - 1) an α,β -unsaturated dicarboxylic compound comprising at least one of a fumaric or maleic ester, wherein the esterifying component comprises a monoalcohol having from 4 to 20 carbon atoms; and
 - 10 2) an olefinically unsaturated compound comprising a monoolefinically unsaturated compound having from 12 to 24 carbon atoms;are reacted in the presence of an effective amount of a polymerization inhibitor.
14. The process according to claim 13, characterized in that component (1) and (2) are reacted in the
15 presence of an effective amount of a polymerization inhibitor and in the substantial absence of a polymerization initiator.
15. The process according to claim 13, characterized in that components (1) and (2) are reacted in the
20 presence of from about 0,01% to about 3% by weight, based upon the combined weight of components (1) and (2), of the polymerization inhibitor.
16. The process according to claim 15, characterized in that components (1) and (2) are reacted in the
presence of from about 0,05% to about 2% by weight, based upon the combined weight of components (1) and (2), of the polymerization inhibitor.
- 25 17. The process according to claim 16, characterized in that components (1) and (2) are reacted in the presence of from about 0,1% to about 1% by weight, based upon the combined weight of components (1) and (2), of the polymerization inhibitor.
- 30 18. The process according to claim 17, characterized in that the polymerization inhibitor comprises at least one of an hydroxy aromatic compound or amine aromatic compound.
19. The process according to claim 18, characterized in that the polymerization inhibitor comprises one or more of hydroquinone, p-tert.butylcatechol and p-hydroxyanisole.
- 35 20. The process according to claim 13, characterized in that components (1) and (2) are reacted in the presence of the at least one polymerization inhibitor at a temperature of from about 180 °C to about 350 °C.
- 40 21. The process according to claim 20, characterized in that components (1) and (2) are reacted in the presence of the at least one polymerization inhibitor at a temperature of from about 200 °C to about 270 °C.
22. The process according to claim 19, characterized in that components (1) and (2) are reacted for from
45 about 0,5 to about 15 hours.
23. The process according to claim 13, characterized in that components (1) and (2) are reacted in molar ratios of from about 0,15/1 to about 6,0/1.
- 50 24. The process according to any one of claims 13-23, characterized in that components (1) and (2) are reacted in the absence of oxygen.
25. A process for producing a composition according to claims 1, wherein
 - 55 1) an α,β -unsaturated dicarboxylic compound comprising at least one of a fumaric or maleic ester, wherein the esterifying component comprises a monoalcohol having from 4 to 20 carbon atoms; and
 - 2) an olefinically unsaturated compound comprising a monoolefinically unsaturated compound having from 12 to 24 carbon atoms;

are reacted under the exclusion of oxygen and in the substantial absence of a polymerization initiator.

26. A process according to any one of claims 13-25, characterized in that the ester component (1) is added to a reaction mixture comprising olefin component (2) by stepwise dosage.

Patentansprüche

1. Zusammensetzung, die sich zur Verwendung als Schmiermittel oder Schmiermittelzusatz eignet und das Reaktionsprodukt (1) einer α,β -ungesättigten Dicarboxylverbindung und (2) einer olefinisch ungesättigten Verbindung enthält, dadurch gekennzeichnet, dass die α,β -ungesättigte Dicarboxylverbindung (1) mindestens einen Fumar- oder Maleinsäureester enthält, in welchem die veresternde Komponente einen Monoalkohol mit 4 bis 20 Kohlenstoffatomen enthält, wobei die olefinisch ungesättigte Verbindung (2) eine monoolefinisch ungesättigte Verbindung mit 12 bis 24 Kohlenstoffatomen enthält, und wobei die Zusammensetzung einen erheblichen Anteil eines Reaktionsprodukts aus (1) und (2) enthält, welches enthält:
 - mindestens 30 Gew.-% eines Produkts (3), das weder das en-Reaktionsprodukt noch das Polymerisationsprodukt von (1) und (2) ist, wobei das Reaktionsprodukt (3) ein intermediäres Molekulargewicht hat, das grösser als dasjenige des entsprechenden en-Reaktionsprodukts und kleiner als dasjenige des entsprechenden Polymerisationsprodukts ist und im Bereich von 600 bis 1500 liegt,
 - bis zu 70 Gew.-% des niedermolekularen en-Reaktionsprodukts der Komponenten (1) und (2), wobei Reaktionsprodukt (3) mit intermediärem Molekulargewicht keine Verbindungen mit mehr als 5 Monomereinheiten enthält.
2. Zusammensetzung nach Anspruch 1, dadurch gekennzeichnet, dass die Komponente (2) ein α -Olefin, ein inneres Olefin, eine Vinylidenverbindung oder einer Mischung hiervon enthält.
3. Zusammensetzung nach Anspruch 2, dadurch gekennzeichnet, dass die Komponente (2) eine Olefinmischung enthält, die als wesentlichen Anteil ein α -Olefin und geringere Anteile eines inneren Olefins und einer Vinylidenverbindung enthält.
4. Zusammensetzung nach Anspruch 2, dadurch gekennzeichnet, dass die Komponente (2) 14 bis 16 Kohlenstoffatome enthält.
5. Zusammensetzung nach Anspruch 1, dadurch gekennzeichnet, dass die Komponente (1) einen Fumarsäure- oder Maleinsäurediester enthält.
6. Zusammensetzung nach Anspruch 5, dadurch gekennzeichnet, dass die Komponente (1) einen Fumarsäurediester enthält.
7. Zusammensetzung nach Anspruch 1, dadurch gekennzeichnet, dass die veresternde Komponente einen Monoalkohol mit 4 bis 8 Kohlenstoffatomen enthält.
8. Zusammensetzung nach Anspruch 7, dadurch gekennzeichnet, dass die veresternde Komponente einen Monoalkohol mit 4 Kohlenstoffatomen enthält.
9. Zusammensetzung nach Anspruch 1, dadurch gekennzeichnet, dass die veresternde Komponente einen alkoxylierten Monoalkohol enthält.
10. Zusammensetzung nach Anspruch 9, dadurch gekennzeichnet, dass der Monoalkohol 1 bis 10 Alkoxyeinheiten, gewählt aus der Gruppe bestehend aus Ethoxy und Propoxy, enthält.
11. Zusammensetzung nach einem der vorangegangenen Ansprüche, dadurch gekennzeichnet, dass sie in einer hydrierten Form vorliegt.
12. Schmiermittel oder Schmiermittelzusatz, enthaltend die Zusammensetzung nach einem der Ansprüche 1-11.

13. Verfahren zur Herstellung einer Zusammensetzung nach Anspruch 1, bei welchem
 - 1) eine α,β -ungesättigte Dicarboxylverbindung, die mindestens einen Fumarsäure- oder Maleinsäureester enthält, in welchem die veresternde Komponente einen Monoalkohol mit 4 bis 20 Kohlenstoffatomen enthält, und
 - 2) eine olefinisch ungesättigte Verbindung, enthaltend eine monoolefinisch ungesättigte Verbindung mit 12 bis 24 Kohlenstoffatomen,in Gegenwart einer wirksamen Menge eines Polymerisationsinhibitors miteinander umgesetzt werden.
14. Verfahren nach Anspruch 13, dadurch gekennzeichnet, dass die Komponenten (1) und (2) in Gegenwart einer wirksamen Menge eines Polymerisationsinhibitors und praktisch in Abwesenheit eines Polymerisationsinhibitors miteinander umgesetzt werden.
15. Verfahren nach Anspruch 13, dadurch gekennzeichnet, dass die Komponenten (1) und (2) in Gegenwart von etwa 0.01 bis etwa 3 Gew.-%, bezogen auf das kombinierte Gewicht der Komponenten (1) und (2), des Polymerisationsinhibitors miteinander umgesetzt werden.
16. Verfahren nach Anspruch 15, dadurch gekennzeichnet, dass die Komponenten (1) und (2) in Gegenwart von etwa 0.05 bis etwa 2 Gew.-%, bezogen auf das kombinierte Gewicht der Komponenten (1) und (2), des Polymerisationsinhibitors miteinander umgesetzt werden.
17. Verfahren nach Anspruch 16, dadurch gekennzeichnet, dass die Komponenten (1) und (2) in Gegenwart von etwa 0.1 bis etwa 1 Gew.-%, bezogen auf das kombinierte Gewicht der Komponenten (1) und (2), des Polymerisationsinhibitors miteinander umgesetzt werden.
18. Verfahren nach Anspruch 17, dadurch gekennzeichnet, dass der Polymerisationsinhibitor mindestens eine aromatische Hydroxyverbindung oder aromatische Aminoverbindung enthält.
19. Verfahren nach Anspruch 18, dadurch gekennzeichnet, dass der Polymerisationsinhibitor eine oder mehrere der Verbindungen Hydrochinon, p-tert-Butylcatechol und p-Hydroxyanisol enthält.
20. Verfahren nach Anspruch 13, dadurch gekennzeichnet, dass die Komponenten (1) und (2) in Gegenwart mindestens eines Polymerisationsinhibitors bei einer Temperatur von etwa 180 bis etwa 350 °C miteinander umgesetzt werden.
21. Verfahren nach Anspruch 20, dadurch gekennzeichnet, dass die Komponenten (1) und (2) in Gegenwart mindestens eines Polymerisationsinhibitors bei einer Temperatur von etwa 200 bis etwa 270 °C miteinander umgesetzt werden.
22. Verfahren nach Anspruch 19, dadurch gekennzeichnet, dass die Komponenten (1) und (2) während etwa 0.5 bis etwa 15 Stunden miteinander umgesetzt werden.
23. Verfahren nach Anspruch 13, dadurch gekennzeichnet, dass die Komponenten (1) und (2) in einem Molverhältnis von etwa 0.15/1 bis etwa 6.0/1 miteinander umgesetzt werden.
24. Verfahren nach einem der Ansprüche 13-23, dadurch gekennzeichnet, dass die Komponenten (1) und (2) in Abwesenheit von Sauerstoff miteinander umgesetzt werden.
25. Verfahren zur Herstellung einer Zusammensetzung nach Anspruch 1, bei dem
 - 1) eine α,β -ungesättigte Dicarboxylverbindung, die mindestens einen Fumarsäure- oder Maleinsäureester enthält, in welchem die veresternde Komponente einen Monoalkohol mit 4 bis 20 Kohlenstoffatomen enthält; und
 - 2) eine olefinisch ungesättigte Verbindung, enthaltend eine monoolefinisch ungesättigte Verbindung mit 12 bis 24 Kohlenstoffatomen,unter Ausschluss von Sauerstoff und praktisch in Abwesenheit eines Polymerisationsinhibitors miteinander umgesetzt werden.
26. Verfahren nach einem der Ansprüche 13-25, dadurch gekennzeichnet, dass die Esterkomponente (1) unter stufenweiser Dosierung zu einer die Olefinkomponente (2) enthaltenden Reaktionsmischung

gegeben wird.

Revendications

- 5 1. Une composition convenant à l'usage en tant que lubrifiant ou additif de lubrifiant, ladite composition comprenant le produit de la réaction de:
 - (1) un composé dicarboxylique α,β -insaturé; et
 - (2) un composé, à insaturation oléfinique;
 caractérisé en ce que le dérivé dicarboxylique α,β -insaturé (1) comprend au moins un des esters
 10 fumariques ou maléiques, dans lequel le dérivé estérifiant comprend un mono-alcool comportant de 4 à 20 atomes de carbone, le composé à insaturation oléfinique (2) comprend un composé à insaturation mono-oléfinique comportant 12 à 24 atomes de carbone, et la composition comprenant une quantité notable du produit de réaction de (1) et de (2) qui comprend:
 - au moins 30% en poids d'un produit (3) qui est ni le produit de réaction ène, ni le produit de polymérisation de (1) et de (2), le produit de réaction (3) ayant un poids moléculaire intermédiaire qui est supérieur à celui du produit de réaction ène correspondant et inférieur à celui du produit de polymérisation correspondant, et qui est compris entre environ 600 et 1500;
 - jusqu'à 70% en poids de produit ène réactionnel des composants (1) et (2) de faible poids moléculaire,
 20 dans lequel le produit de réaction de poids moléculaire intermédiaire (3) ne comprend pas des composés comportant plus de cinq unités monomères.
2. La composition selon la revendication 1, caractérisé en ce que le composant (2) comprend un dérivé α -oléfinique, oléfinique interne, vinylidénique ou leurs mélanges.
- 25 3. La composition selon la revendication 2, caractérisé en ce que le composant (2) comprend un mélange d'oléfines comprenant en majeure partie une α -oléfine et avec des quantités mineures de dérivés oléfiniques internes et vinylidéniques.
- 30 4. La composition selon la revendication 2, caractérisée en ce que le composant (2) comprend de 14 à 16 atomes de carbone.
5. La composition selon la revendication 2, caractérisée en ce que le composant (1) comprend un diester fumarique ou maléique.
- 35 6. La composition selon la revendication 5, caractérisée en ce que le composant (1) comprend un diester fumarique.
7. La composition selon la revendication 1 caractérisée en ce que le constituant estérifiant comprend un monoalcool comportant de 4 à 8 atomes de carbone.
- 40 8. La composition selon la revendication 7, caractérisée en ce que le constituant estérifiant comprend un monoalcool comportant 4 atomes de carbone.
- 45 9. La composition selon la revendication 1, caractérisée en ce que le constituant estérifiant comprend un monoalcool alcoylé.
10. La composition selon la revendication 9, caractérisée en ce que le monoalcool comprend 1 à 10 unités alcoxy choisies dans le groupe consistant en éthoxy et propoxy.
- 50 11. La composition selon l'une quelconque des revendications précédentes, caractérisée en ce qu'elle se trouve sous une forme hydrogénée.
12. Un lubrifiant ou additif de lubrifiant comprenant une composition selon l'une quelconque des revendications 1 à 11.
- 55 13. Un procédé de préparation d'une composition selon la revendication 1, dans lequel:

- (1) un dérivé dicarboxylique α,β -insaturé; comprenant au moins l'un des esters fumariques ou maléiques, dans lequel le constituant estérifiant comprend un monoalcool comportant de 4 à 20 atomes de carbone, et
 (2) un dérivé à insaturation oléfinique comprenant un composé à insaturation mono-oléfinique comportant de 12 à 24 atomes de carbone,
 5 sont mis à réagir en présence d'une quantité efficace d'un inhibiteur de polymérisation.
14. Le procédé selon la revendication 13, caractérisé en ce que l'on fait réagir les constituants (1) et (2) en présence d'une quantité efficace d'un inhibiteur de polymérisation et pratiquement en l'absence
 10 d'initiateur de polymérisation.
15. Le procédé selon la revendication 13, caractérisé en ce que l'on fait réagir les constituants (1) et (2) en présence d'environ 0,01 % à environ 3% en poids, exprimés par rapport aux poids combinés des constituants (1) et (2), d'un inhibiteur de polymérisation.
 15
16. Le procédé selon la revendication 15, caractérisé en ce que l'on fait réagir les constituants (1) et (2) en présence d'environ 0,05% à environ 2% en poids, exprimés par rapport aux poids combinés des constituants (1) et (2), d'un inhibiteur de polymérisation.
- 20 17. Le procédé selon la revendication 16, caractérisé en ce que l'on fait réagir les constituants (1) et (2) en présence d'environ 0,1% à environ 1% en poids, exprimés par rapport aux poids combinés des constituants (1) et (2), d'un inhibiteur de polymérisation.
- 25 18. Le procédé selon la revendication 17, caractérisé en ce que l'inhibiteur de polymérisation comprend au moins un choisi parmi les composés hydroxyaromatiques ou aminoaromatiques.
19. Le procédé selon la revendication 18, caractérisé en ce que l'inhibiteur de polymérisation comprend un ou plusieurs composés choisis parmi hydroquinone, paratert.butyl-catéchol et parahydroxy-anisole.
- 30 20. Le procédé selon la revendication 13, caractérisé en ce que l'on fait réagir les constituants (1) et (2) en présence d'au moins un inhibiteur de polymérisation à une température comprise entre environ 180 °C et environ 350 °C.
- 35 21. Le procédé selon la revendication 20, caractérisé en ce que l'on fait réagir les constituants (1) et (2) en présence d'au moins un inhibiteur de polymérisation à une température comprise entre environ 200 °C et environ 270 °C.
22. Le procédé selon la revendication 19, caractérisé en ce que l'on fait réagir les constituants (1) et (2) pendant environ 0,5 à environ 15 heures.
 40
23. Le procédé selon la revendication 13, caractérisé en ce que l'on fait réagir les constituants (1) et (2) en des rapports molaires compris entre environ 0,15/1 et environ 6,0/1.
- 45 24. Le procédé selon l'une quelconque des revendications 13 à 23, caractérisé en ce que l'on fait réagir les constituants (1) et (2) à l'abri de l'oxygène.
25. Un procédé de préparation d'une composition selon la revendication 1, dans lequel on fait réagir:
 (1) un dérivé dicarboxylique α,β -insaturé comprenant au moins l'un des esters fumariques ou maléiques, dans lequel le constituant estérifiant comprend un monoalcool comportant de 4 à 20
 50 atomes de carbone, et
 (2) un dérivé à insaturation oléfinique comprenant un composé à insaturation mono-oléfinique comportant de 12 à 24 atomes de carbone,
 à l'abri de l'oxygène et pratiquement en l'absence d'initiateur de polymérisation.
- 55 26. Un procédé selon l'une quelconque des revendications 13 à 25, caractérisé en ce que le constituant ester (1) est ajouté au mélange réactionnel comprenant le constituant oléfinique (2) par addition progressive.